

MIRAGE

Massimo Farinatti

GHOST

MLS



video

Specchio a luce diretta con tecnologia GHOST e MLS

Interruttore touch illuminato ON/OFF con cambio colore e funzione dimmer

Spessore specchio 5mm

Pellicola di sicurezza

Funzione antiappannamento

Temperatura colore TripleWhite

3000, 4000 o 6000K

Montaggio orizzontale o verticale

220V, CE, IP44

Direct light mirror with GHOST and MLS technology

Illuminated touch ON/OFF sensor color change and dimmer function

5mm mirror thickness

Safety film backing

Defogger function

TripleWhite temperature color

3000, 4000 or 6000K

Vertical or horizontal fixing

220V, CE, IP44.

	code	a	b	c	plus
	BR 6080 730 G	600	800	40	
	BR 80100 731 G	800	1000	40	
	BR 80120 732 G	800	1200	40	
	BR 80140 733 G	800	1400	40	
	BR 80160 734 G	800	1600	40	




MIRAGE OVAL

Massimo Farinatti

GHOST
MLS

Specchio a luce diretta con tecnologia GHOST e MLS
Interruttore touch illuminato ON/OFF con cambio colore e funzione dimmer
Spessore specchio 5mm
Pellicola di sicurezza
Funzione antiappannamento
Temperatura colore TripleWhite 3000 - 4000 o 6000K
Montaggio orizzontale o verticale
220V, CE, IP44

Direct light mirror with GHOST and MLS technology
 Illuminated touch ON/OFF sensor color change and dimmer function
 5mm mirror thickness
 Safety film backing
 Defogger function
 TripleWhite temperature color 3000 - 4000 or 6000K
 Vertical or horizontal fixing
 220V, CE, IP44



code	a	b	c	plus
BO 9045 738 G	900	450	40	



Mirage Round

Massimo Farinatti

GHOST

MLS

Specchio a luce LED diretta con tecnologia GHOST e MLS
Interruttore touch illuminato ON/OFF con cambio colore e funzione dimmer
Mensola in metallo nero opaco
Spessore specchio 5mm
Pellicola di sicurezza
Funzione antiappannamento
Temperatura colore TripleWhite 3000 - 4000 o 6000K
220V, CE, IP44.

Direct LED light mirror with GHOST and MLS technology
 Illuminated touch ON/OFF sensor color change and dimmer function,
 Black metal shelf
 5mm mirror thickness
 Safety film backing
 Defogger function
 Triple White temperature color 3000 - 4000 or 6000K
 220V, CE, IP44.

	code	color	∅	c	plus
	BT 0080 735 G	●	800	40/120	
	BT 0100 736 G	●	1000	40/120	
	BT 0120 737 G	●	1200	40/120	

